

SAFETY DATA SHEET

Version 8.9
Revision Date 01.03.2023
Print Date 02.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Ethanol

CAS-No. : 64-17-5

1.2 Other means of identification

No data available

1.3 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Biochemical research/analysis, Reagent for analysis

1.4 Details of the supplier of the safety data sheet

Company : ZHENGZHOU BATONG INDUSTRIAL CO., LTD
GUAN DI MIAO Village, YU
LONG Town, XING YANG
City ZhengZhou City HeNan
Province CHINA

Telephone : +86 0371 6853-8712

1.5 Emergency telephone

Emergency Phone # : +86 0371 6853-8606

SECTION 2: Hazards identification

2.1 GHS Classification

Flammable liquids (Category 2), H225

Serious eye damage/eye irritation (Category 2A), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word : Danger

Hazard statement(s)

H225

Highly flammable liquid and vapor.

H319

Causes serious eye irritation.

Precautionary statement(s)

Prevention

- P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P280 Wear protective gloves/ eye protection/ face protection.

Response

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage

- P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal

- P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards - none

SECTION 3: Composition/information on ingredients

Substance / Mixture : Substance

3.1 Substances

- Formula : C₂H₆O
Molecular weight : 46.07 g/mol
CAS-No. : 64-17-5
EC-No. : 200-578-6

Hazardous ingredients

Component	Classification	Concentration
ethanol	Flam. Liq. 2; Eye Dam./Irrit. 2A; H225, H319 Concentration limits: >= 50 %: Eye Irrit. 2A, H319;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb®).

Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.
For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.3 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m ³	Australia. Workplace Exposure Standards for Airborne Contaminants.

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min
Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 120 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---|---|
| a) Physical state | liquid |
| b) Color | colorless |
| c) Odor | alcohol-like |
| d) Melting point/freezing point | Melting point/freezing point: -114.0 °C at 1,013.25 hPa |
| e) Initial boiling point and boiling range | 78.29 °C at 1,013 hPa |
| f) Flammability (solid, gas) | No data available |
| g) Upper/lower flammability or explosive limits | Upper explosion limit: 27.7 %(V)
Lower explosion limit: 3.1 %(V) |
| h) Flash point | 13 °C - closed cup |
| i) Autoignition temperature | 363 - 425 °C
at 1,013 hPa |
| j) Decomposition temperature | Distillable in an undecomposed state at normal pressure. |
| k) pH | 7.0 at 10 g/l at 20 °C |
| l) Viscosity | Viscosity, kinematic: No data available
Viscosity, dynamic: 1.2 mPa.s at 20 °C |

- | | |
|--|--|
| m) Water solubility | 1,000 g/l at 20 °C - completely miscible |
| n) Partition coefficient:
n-octanol/water | log Pow: -0.35 at 24 °C - Bioaccumulation is not expected. |
| o) Vapor pressure | 57.26 hPa at 19.6 °C |
| p) Density | 0.79 g/cm ³ at 20 °C |
| Relative density | No data available |
| q) Relative vapor
density | No data available |
| r) Particle
characteristics | No data available |
| | |
| s) Explosive properties | No data available |
| t) Oxidizing properties | none |

9.2 Other safety information

Conductivity	< 1 µS/cm
Surface tension	22.31 mN/m at 20 °C - similar to water
Relative vapor density	1.6

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion/exothermic reaction with:

hydrogen peroxide
perchlorates
perchloric acid
Nitric acid
mercury(II) nitrate
permanganic acid
Nitriles
peroxi compounds
Strong oxidizing agents
nitrosyl compounds
Peroxides
sodium
Potassium
halogen oxides
calcium hypochlorite
nitrogen dioxide
metallic oxides
uranium hexafluoride
iodides
Chlorine

Alkali metals
Alkaline earth metals
alkali oxides
Ethylene oxide
silver
with
Nitric acid
silver compounds
with
Ammonia
potassium permanganate
with
conc. sulfuric acid
Risk of ignition or formation of inflammable gases or vapours with:
halogen-halogen compounds
chromium(VI) oxide
chromyl chloride
Fluorine
hydrides
Oxides of phosphorus
platinum
Nitric acid
with
potassium permanganate

10.4 Conditions to avoid

Warming.
Warming.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 10,470 mg/kg
(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 124.7 mg/l - vapor

(OECD Test Guideline 403)

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

(OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Remarks: (in analogy to similar products)

The value is given in analogy to the following substances: Methanol

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: dominant lethal test

Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 478

Result: Positive results were obtained in some in vivo tests.

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male - Oral - NOAEL (No observed adverse effect level) - 1,730 mg/kg - LOAEL (Lowest observed adverse effect level) - 3,200 mg/kg

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish

flow-through test LC50 - Pimephales promelas (fathead minnow) - 15,300 mg/l - 96 h

	(US-EPA)
Toxicity to daphnia and other aquatic invertebrates	static test LC50 - Ceriodaphnia dubia (water flea) - 5,012 mg/l - 48 h Remarks: (ECHA)
Toxicity to algae	static test ErC50 - Chlorella vulgaris (Fresh water algae) - 275 mg/l - 72 h (OECD Test Guideline 201)
Toxicity to bacteria	static test IC50 - activated sludge - > 1,000 mg/l - 3 h (OECD Test Guideline 209)
Toxicity to fish(Chronic toxicity)	semi-static test NOEC - Danio rerio (zebra fish) - 250 mg/l - 120 h Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	semi-static test NOEC - Daphnia magna (Water flea) - 9.6 mg/l - 9 d Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 15 d Result: ca.95 % - Readily biodegradable. (OECD Test Guideline 301E)
Biochemical Oxygen Demand (BOD)	930 - 1,670 mg/g Remarks: (Lit.)
Theoretical oxygen demand	2,100 mg/g Remarks: (Lit.)

12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No interference with wastewater treatment plants are to be expected when used properly. Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information**14.1 UN number**

ADR/RID: 1170 IMDG: 1170 IATA-DGR: 1170

14.2 UN proper shipping nameADR/RID: ETHANOL
IMDG: ETHANOL
IATA-DGR: Ethanol**14.3 Transport hazard class(es)**

ADR/RID: 3 IMDG: 3 IATA-DGR: 3

14.4 Packaging group

ADR/RID: II IMDG: II IATA-DGR: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA-DGR: no

14.6 Special precautions for user

None

14.7 Incompatible materials**Other regulations**

Hazchem Code : •2YE

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Standard for the Uniform Scheduling of Medicines and Poisons : No poison schedule number allocated

SECTION 16: Other information**-Full text of H-Statements referred to under sections 2 and 3.**H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.**Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. ZHENGZHOU BATONG INDUSTRIAL CO., LTD and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See <https://www.batongchemical.com> and/or the reverse side of the invoice or packing slip for additional terms and conditions of sale.